



**Salt Lake Community College**

4600 S. Redwood Rd.

Salt Lake City, UT

**Request For Quotation**

6025.2-3

Date: December 19, 2010

<p>Vendor:  Rosemount: Puffer-Sweiven <a href="http://www.Puffer.com">www.Puffer.com</a>  Yokogawa: <a href="http://www.techstaris.com">www.techstaris.com</a>  Honeywell: <a href="mailto:dlamance@wilsonmohr.com">dlamance@wilsonmohr.com</a>  Other Qualified Vendors</p>	<p>Notes:  Don Day (<a href="mailto:day@letton-hall.com">day@letton-hall.com</a>)  Eric Kelner (<a href="mailto:kelner@letton-hall.com">kelner@letton-hall.com</a>)</p>
--	---

Quantity	Description	Unit Price	Extension
2	<p>Transmitter, Static Pressure indicating, -200 to +400 In, H2O calibrated range, two 1/2" electrical entries w/plugs, 4-20 mA digital Hart Smart output. 316SS isolating diaphragm, glass filled PTFE o'rings, silicone filled, LCD display, Calibration datasheet, fitted with two valve co-planer-manifold. 2" pipe-stand mounting bracket."</p> <p>Tag # 3-PIT-100 3-PIT-200</p>		
2	<p>"Transmitter, temperature indicating, with 0-150 Deg. F calibrated range, 1/2in. electrical entry, 4-20 mA Hart smart output, 304SS thermal-well for 3/4in. Pipe entry, 2-1/2in. "U" length with 4-wire 100 Ohm RTD, LCD transmitter display."</p> <p>Tag # 3-TIT-100 3-TIT-200</p>	<p>Sub Total Shipping Tax(es)  Total</p>	



**Request For Quotation**

245 NE 30 Rd.

6027.1-3

Great Bend KS, 67530

Date: December 19, 2010

<p>Vendor:          Rosemount: Puffer-Sweiven <a href="http://www.Puffer.com">www.Puffer.com</a>          Yokogawa: <a href="http://www.techstaris.com">www.techstaris.com</a>          Honeywell: dlamance@wilsonmohr.com          Other Qualified Vendors</p>	<p>Notes:          Don Day (day@letton-hall.com)          Eric Kelner (kelner@letton-hall.com)</p>
---	--

Quantity	Description	Unit Price	Extension
4	<p>Transmitter, Static Pressure indicating, -200 to +400 In, H2O calibrated range, two 1/2" electrical entries w/plugs, 4-20 mA digital Hart Smart output. 316SS isolating diaphragm, glass filled PTFE o'rings, silicone filled, LCD display, Calibration datasheet, fitted with two valve co-planer-manifold. 2" pipe-stand mounting bracket."</p> <p>Tag # 1-PIT-100            1-PIT-200            2-PIT-100            2-PIT-200</p>		
4	<p>"Transmitter, temperature indicating, with 0-150 Deg. F calibrated range, 1/2in. electrical entry, 4-20 mA Hart smart output, 304SS thermal-well for 3/4in. Pipe entry, 2-1/2in. "U" length with 4-wire 100 Ohm RTD, LCD transmitter display."</p> <p>Tag # 1-TIT-100            1-TIT-200            2-TIT-100            2-TIT-200</p>	<p>Sub Total            Shipping            Tax(es)</p> <p>Total</p>	